



(43) International Publication Date
17 February 2005 (17.02.2005)

PCT

(10) International Publication Number
WO 2005/015035 A1

- (51) **International Patent Classification⁷:** **F16C 33/10** (81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) **International Application Number:** PCT/EP2004/009096

(22) **International Filing Date:** 12 August 2004 (12.08.2004)

(25) **Filing Language:** English

(26) **Publication Language:** English

(30) **Priority Data:**
1024091 12 August 2003 (12.08.2003) NL

(71) **Applicant** (*for all designated States except US*): **AB SKF** [SE/SE]; Hornsgatan 1, S-415 50 Göttenborg (SE).

(72) **Inventors; and**

(75) **Inventors/Applicants** (*for US only*): **IOANNIDES**, Eusthassios [GR/NL]; Montessorilaan 9, NL-3706 TB Zeist (NL). **SPIKES**, Hugh, Alexander [GB/GB]; Flat 3, Lexham Gardens, London W8 5JJ (GB). **BRAJIC-MITIDIERI**, Petra [HR/GB]; 56D Caversham Road, London, NW 2DR (GB). **GOSMAN**, Allen, David [GB/GB]; 15 Home Park Road, London, SW 19 (GB).

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

 - *with international search report*
 - *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*


For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SLIDING BEARING WITH IMPROVED SURFACE TOPOGRAPHY



- (57) Abstract:** A sliding bearing comprises two opposite bearing surfaces (3, 4) which enclose a gap (6) containing a lubricant film (5), said bearing surfaces (3, 4) being moveable with respect to each other in a generally parallel fashion, at least one of said surfaces (4) being provided with at least one cavity (10), said cavity having a depth (h3) which is at least equal to the lubricant film thickness. One of the length (Bp) and width (Lp) dimension of the surface area of said cavity (10) amounts to at least 100 μm .

WO 2005/015035 A1